




DataPower Series

ONLINE DOUBLE CONVERSION UPS

10kVA To 20kVA (0.9 PF)

3 PH input/1 PH output (3:1)

Tower



Control Panel

Features

- N+X parallel redundancy
- Online double conversion with DSP control
- Input current harmonic: <5%
- Optimization battery group, the quantity of battery: 16/18/20 pieces (optional)
- factor is changed when selection different battery quantity 16pc:0.7PF;18PCS:0.8PF;20PCS:0.9PF
- Wide input voltage range: 208~478Vac
- Wide input frequency range(50Hz: 45~55Hz / 60Hz: 54~66Hz)
- Support generator input
- Support economic(ECO) operation mode
- Self-testing when UPS startup
- Options: SNMP card/Relay card/ Parallel board
- Cold start



Rear Panel



Relay card



SNMP



Parallel board



Battery Cabinets
(Optional)

Technical Specifications:

MODEL	DPS-10K3-1	DPS-15K3-1	DPS-20K3-1
Capacity (VA/Watts)	10k / 9k	15k / 13.5k	20k / 18k
INPUT			
Nominal voltage	380/400/415Vac;(3Ph+N+PE)		
Operating voltage range	208 ~ 478Vac		
Operating frequency range	50Hz:45~55Hz;60Hz:54~66Hz(auto sensing)		
Power factor	≥0.99		
Bypass voltage range	Max.voltage: 220V: +25%(optional +10%,+15%,+20%) 230V: +20% (optional +10%,+15%) 240V: +15% (optional +10%) Min.voltage: -45% (optional -20%,-30%)		
Bypass frequency range	Frequency protection range: ± 10%		
ECO range	Same as the bypass		
Harmonic distortion (THDi)	<5%(100% linear load)		
Generator input	Support		
OUTPUT			
Rated voltage	220/230/240Vac		
Power factor	0.9		
Voltage regulation	± 1%		
Frequency	Line Mode	± 1%/ ± 2%/ ± 4%/ ± 5%/ ± 10% of the rated frequency(optional)	
	Bat. Mode	50/60(± 0.1)Hz	
Crest factor	3:1		
Harmonic distortion (THDv)	≤2% with linear load ≤5% with non-linear load		
Efficiency	>93.5%		>94.5%
BATTERY			
Battery voltage	± 96/108/120Vdc (optional)		
Capacity (standard unit)	12V/7Ah/9Ah		
Typical recharge time	6~8 hours (to 90% of full capacity)		
Charge current	1A(10kVA Standard unit) ; Max.current 10A(Long run unit)		
SYSTEM FEATURES			
Transfer time	Mains to Battery:0ms; Mains to Bypass:0ms		
Overload	Line Mode	Load≤110%: last 60min, ≤125%: last 10min, ≤150%: last 1min, >150% turn to bypass mode immediately	
	Bypass Mode	63A(Breaker)	100A(Breaker)
Short circuit	Hold Whole System		
Overheat	Line Mode: Turn to Bypass; Bat. Mode: Shut down UPS immediately		
Low battery voltage	Alarm and Switch off		
Self-diagnostics	Upon Power On and Software Control		
Battery	Advanced Battery Management		
Audible & Visual alarms	Line Failure, Battery Low, Overload, System Fault		
LED & LCD display	Line Mode, Bat. Mode, Eco Mode, Bypass Mode, Battery Low, Overload & UPS Fault		
LCD display	Input Voltage, Input Frequency, Output Voltage, Output Frequency, Load Percentage, Battery Voltage, Inner Temperature & Remaining Battery Backup Time		
Communication interface	RS232,USB,SNMP card(optional), Parallel board(optional), Relay card (optional)		
ENVIRONMENTAL			
Operating temperature	0°C ~ 40°C		
Storage temperature	-25°C ~ 55°C		
Humidity range	0 ~ 95% (non-condensing)		
Altitude	< 1500m		
Noise level	<55dB		<58dB
PHYSICAL			
Dimension D × W × H (mm)	597 × 250 × 655(S)/502 × 250 × 616(H)	502 × 250 × 616	
Net weight (kg)	76(S)/35 (H)	45	46
STANDARDS			
Safety	IEC/EN62040-1,IEC/EN60950-1		
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4, IEC61000-4-5,IEC61000-4-6,IEC61000-4-8		
BATTERY BANK			
Model	DPS-BT Series		
Battery type& Max.quantity	2 × 20pcs/7Ah(9Ah)		
PHYSICAL OF BATTERY BANK			
Dimensions D × W × H (mm)	597 × 250 × 616		
Net weight (kg)	122/134		

Specifications are subject to change without prior notice.